



KARL SCHUKE BERLINER ORGELBAUWERKSTATT GMBH

I. Specification

I. Man. Great, C-a^{'''}, 75 mm WS

1	Bourdon	16'	C-H wood	58	KI / 20%
2	Principal	8'	Facade	58	80 %
3	Rohrflöte	8'		58	30 %
4	Oktav	4'		58	75 %
5	Gemshorn	4'		58	75 %
	Oktav	2'	from Mixtur		
6	Mixtur 4f	2'		232	75 %
7	Trompete	8'		58	75 %
	Tremulant				

II. Man. Swell (in swell box), C-a^{'''}, 85 mm WS

8	Flauto amabile	8'	C-h'' wood	58	KI / 30 %
9	Gamba	8'		58	75 %
10	Vox coelestis	8'		46	75 %
11	Fugara	4'		58	75 %
12	Flûte octav.	4'	wood, harmonized from f ^o	58	KI / AH
13	Nazard	2 2/3'	harmonized from c'	58	30 %
14	Oktavin	2'	stopped, harmonized from c ^o	58	75 %
15	Tierce	1 3/5'	harmonized	58	30 %
16	Basson-Hautbois	8'		58	75 %
	Tremulant				

Pedal C-f' 75/95 mm WS

17	Subbaß	16'	wood	30	KI
	Bourdon	16'	Transm. HW		
	Principal	8'	Transm. HW		
18	Violoncelle	8'		30	75 %
	Rohrflöte	8'	Transm. HW		
	Oktav	4'	Transm HW		
19	Posaune	16'	wood C-F half length	30	KI
	Trompete	8'	Transm HW		

mechanical Couplers: II-I, II-P, I-P, II-P 4'